

Date of approval: May 2020

No.	Related Documents	Status *
1	Latest tide table	Active
2	ISPS ship pre-arrival form (F-51/52.001)	Active
3	Maritime Declaration of Health form (F-51/52.021)	
4	Questions related to the novel Coronavirus (COVID-19) outbreak (F51/52.034)	Active
5	Questions related to the Ebola outbreak (F51/52.027)	Active
6	Shipping notice 2016/01 Minimum requirements for safe and efficient passage of sea-going vessels in Surinamese waters	Active
7	Shipping notice 2018/03 nautical Accessibility Suriname River	Active
8	Shipping notice 2018/05 Accessibility Kuldipsingh Jetty	Expired and replaced by Shipping notice 2020/05
9	Chart no 2675 Suriname River from Entrance to Toevlucht and corresponding ENC's no. SR2218A and no.SR2218	Active
10	Relevant NtM of the area on www.mas.sr	Active

Additional requirements for ships to navigate alongside Kuldipsingh Jetty

### 1. Length overall (LOA)

Kuldipsingh Jetty can accommodate vessels with a maximum length of two hundred twenty-five meters (225m)

### 2. Depth at berth

The berthing area from the channel to the jetty is subdivided into three zones (see appendix 1). Zone 1A and Zone 1B covers the area where vessels are moored at Kuldipsingh Jetty and Zone 2 covers the area of approach from the channel to Zone1.

Zone 1A **south side**: has a depth of 4.3 meters at Low Water Spring

Zone 1B **north side**: has a depth of 3 meters at Low Water Spring

Zone 2: has a depth of 4.6 meters at Low Water Spring

**The calculated vessel draft in Zone 1A:**

- Vessels mooring and departing at starboard and port side is; 4.3m- 0.20m (keel clearance) = 4.1m + tidal rise calculated at the time of mooring.

**The calculated vessel draft in Zone 1B:**

- Vessels mooring and departing at starboard and port side is; 3m- 0.20m (keel clearance) = 2.8m + tidal rise calculated at the time of mooring.

**3. Tugboat Assistance**

- Vessels less than one hundred and forty meters (140m) in length are not required to have bow thrusters and tugboat assistance;
- Vessels less than one hundred and fifty meters (150m) in length with bow thrusters are not required to have tugboat assistance;
- Vessels of one hundred and forty meters (140m) up to one hundred and sixty meters (160m) in length without bow thrusters are required to have tugboat assistance with a minimum capacity of fifteen hundred Horsepower (1500HP);
- Vessels more than one hundred and sixty meters (160m) up to one hundred and eighty meters (180m) in length are required to have at least one (1) tugboat for assistance with a minimum capacity of two thousand horsepower (2000HP).
- In special or exceptional cases, the MAS is fully authorized to request tugboat assistance for partial or the entire distance to be navigated within the channel.

**Note:**

- **In special or exceptional cases, the MAS is fully authorized to request tugboat assistance for partial or the entire distance to be navigated within the channel Vessels with bow thrusters which are not in good working condition are regarded as vessels without bow thrusters.**
- **A mooring boat must be on standby to assist with the mooring lines.**
- **For tugboat assistance tugboat operators/companies should possess a valid license for tugboat operations issued by the Maritime Authority Suriname.**
- **Vessels of more than one hundred and twenty metres (120m) in length shall use the turning basin or anchorage area at Chatillion or Simonspolder (for turning) to be able to moor Port side at the Jetty.**

**Bathymetric survey for monitoring the depth at Kuldipsingh Jetty**

**Due to the rapid sedimentation rate periodic maintenance is required. The Maritime Authority Suriname will issue the depth at Kuldipsingh Jetty on quarterly basis after each bathymetric survey. The latest depth survey Kuldipsingh Jetty dated October 2019 (depths are referred to LWS) is shown as an attachment in figure.**

**Approved by the  
Maritime Authority Suriname,**

**Mr. M. Amafo LL.M  
Director**

Appendix 1:

